



型名 Type Number	F4052A		
定格 Rating	15A~30A		
ねじ径 Screw Diameter	M3		
使用可能電流 Usable Current	15A	20A	30A
適合電線 Compatible Wire	1.25mm <sup>2</sup>	2mm <sup>2</sup>	3.5mm <sup>2</sup>
推奨圧着端子 Recommended Crimp Terminal	R1.25-3	R2-3	※R3.5-4

一般公差/General Tolerance ±0.5  
 尺度<sup>2</sup>/<sub>1</sub>Scale<sup>2</sup>/<sub>1</sub> 単位/Unit mm

※適合電線3.5mm<sup>2</sup>使用時の圧着端子は"R3.5-4"で使用可能  
 The crimp terminal when using the compatible wires 3.5mm<sup>2</sup> can be used with "R3.5-4".  
 推奨圧着端子はニチフ(株)の圧着端子を基に選定しています。  
 The crimp terminals are selected based on the crimp terminals from Nichifu Co., Ltd.

・注文方法: **型番** --- (下表の型番を御参照下さい。)

・Ordering Form: **Type No.** (See the type number in the following table)

### 仕様 Specifications

番号 Part No.	名称 Part Name	材質 Material	寸法 Size	規格 Standard	処理 Treatment
1	基板端子 Printed board Terminal	黄銅 Brass	板厚 t=0.8	C2680R	スズメッキ Tin-Plated
2	結線ビス Screw	黄銅 Brass	M3	C2700W	ニッケルメッキ Nickel-Plated

型番 Type No.	納入される物 Product Delivered
F4052A	基板端子(M3用)のみ(ビスなし) Printed board terminal (for M3) only (W/O screws)
F4052AS	基板端子M3×6Lバインドビス(Type⑧)組付 Printed board terminal+M3×6L binding head attached (Type⑧)

対応可能ビス Compatible screw	材質 Material	処理 Treatment	形状 Shape
PW. SWセムスパインド M3×6L Type③With Plain(Flat)washer and spring lock washer M3×6L	黄銅 Brass	ニッケルメッキ Nickel-Plated	Type③
	鉄 steel		
SWセムスパインド M3×6L Type④With spring lock washer M3×6L	黄銅 Brass	ニッケルメッキ Nickel-Plated	Type④
PW. SWセムスナベ M3×7L Type⑤With Plain(Flat)washer and spring lock washer M3×7L	黄銅 Brass	ニッケルメッキ Nickel-Plated	Type⑤
	鉄 steel		
SWセムスナベ M3×7L Type⑦With spring lock washer M3×7L	黄銅 Brass	ニッケルメッキ Nickel-Plated	Type⑦