


| | | | |
|--------------------------------------|------------------------|-------------------|----------------------|
| 型名 Type Number | F 4 1 4 6 A | | |
| 定格 Rating | 1 5 A ~ 3 0 A | | |
| ねじ径 Screw Diameter | M 3 | | |
| 使用可能電流 Usable Current | 1 5 A | 2 0 A | 3 0 A |
| 適合電線 Compatible Wire | 1. 2 5 mm ² | 2 mm ² | 3. 5 mm ² |
| 推奨圧着端子 Recommended Crimp Terminal | R 1. 2 5-3 | R 2-3 | R 3. 5-4 |

一般公差 / General Tolerance ±0.5

尺度 / Scale 2/1 単位 / Unit mm

基板加工参考例
Processing the reference printed board



プリント基板厚:t=1.6~2.0
Printed board:t=1.6~2.0

・注文方法: **型番** (下表の型番を御参照下さい。)

■仕様 Specifications. ・Ordering Form: Type No. (See the type number in the following table)

| 番号 Part No. | 名称 Part Name | 材質 Material | 寸法 Size | 規格 Standard | 処理 Treatment |
|-------------|-----------------------------|-------------|----------|-------------|-----------------------|
| 1 | 基板端子 Printed board Terminal | 黄銅 Brass | 板厚 t=1.0 | C2680R | スズメッキ Tin-Plated |
| 2 | 結線ビス Screw | 黄銅 Brass | M3 | C2700W | ニッケルメッキ Nickel-Plated |

| 型番 Type No. | 納入される物 Product Delivered |
|-------------|---|
| F4146A | 基板端子(M3用)のみ(ビスなし) Printed board terminal (for M3) only (W/O screws) |
| F4146AS | 基板端子M3×6Lバインドビス(Type⑧)組付 Printed board terminal+M3×6L binding head attached (Type⑧) |

| 対応可能ビス Compatible screw | 材質 Material | 処理 Treatment | 形状 Shape |
|--|-------------|-----------------------|----------|
| PW, SWセムスパインド M3×6L Type③ With Plain (Flat) washer and spring lock washer M3×6L | 鉄 steel | ニッケルメッキ Nickel-Plated | Type③ |
| SWセムスパインド M3×6L Type④ With spring lock washer M3×6L | 鉄 steel | ニッケルメッキ Nickel-Plated | Type④ |
| PW, SWセムスナベ M3×7L Type⑤ With Plain (Flat) washer and spring lock washer M3×7L | 鉄 steel | ニッケルメッキ Nickel-Plated | Type⑤ |
| SWセムスナベ M3×7L Type⑦ With spring lock washer M3×7L | 鉄 steel | ニッケルメッキ Nickel-Plated | Type⑦ |