


型名 Type Number	F 4 1 4 6 C		
定格 Rating	1 5 A ~ 3 0 A		
ねじ径 Screw Diameter	M 4		
使用可能電流 Usable Current	1 5 A	2 0 A	3 0 A
適合電線 Compatible Wire	1. 2 5 mm ²	2 mm ²	3. 5 mm ²
推奨圧着端子 Recommended Crimp Terminal	R 1. 2 5-4	R 2-4	R 3. 5-4

一般公差 / General Tolerance ±0.5

尺度 / Scale 2/1 単位 / Unit mm

基板加工参考例
Processing the reference printed board



プリント基板厚:t=1.6~2.0
Printed board:t=1.6~2.0

・注文方法: **型番** (下表の型番を御参照下さい。)

■仕様 Specifications. •Ordering Form: Type No. (See the type number in the following table)

番号 Part No.	名称 Part Name	材質 Material	寸法 Size	規格 Standard	処理 Treatment
1	基板端子 Printed board Terminal	黄銅 Brass	板厚 t=1.0	C2680R	スズメッキ Tin-Plated
2	結線ビス Screw	黄銅 Brass	M4	C2700W	ニッケルメッキ Nickel-Plated

型番 Type No.	納入される物 Product Delivered
F4146C	基板端子(M4用)のみ(ビスなし) Printed board terminal (for M4) only (W/O screws)
F4146CS	基板端子M4×6Lバインドビス(Type⑧)組付 Printed board terminal+M4×6L binding head attached (Type⑧)

対応可能ビス Compatible screw	材質 Material	処理 Treatment	形状 Shape
PW, SWセムスパインド M4×6L Type③With Plain (Flat) washer and spring lock washer M4×6L	鉄 steel	ニッケルメッキ Nickel-Plated	Type③
SWセムスパインド M4×6L Type④With spring lock washer M4×6L	鉄 steel	ニッケルメッキ Nickel-Plated	Type④
PW, SWセムスナベ M4×7L Type⑤With Plain (Flat) washer and spring lock washer M4×7L	鉄 steel	ニッケルメッキ Nickel-Plated	Type⑤
SWセムスナベ M4×7L Type⑦With spring lock washer M4×7L	鉄 steel	ニッケルメッキ Nickel-Plated	Type⑦