



型名 Type Number	FP439A		
定格 Rating	20A~40A		
ねじ径 Screw Diameter	M3		
使用可能電流 Usable Current	20A	30A	40A
適合電線 Compatible Wire	2mm ²	5.5mm	
推奨圧着端子 Recommended Crimp Terminal	R2-3	※R5.5-3M	

一般公差 / General Tolerance ±0.5

尺度 / Scale $\frac{2}{1}$ 単位 / Unit mm

※適合電線5.5mm²使用時の圧着端子は“R5.5-3M”で使用可能
The crimp terminal when using the compatible wires 5.5mm² can be used with “R5.5-3M”.

推奨圧着端子はニチフ(株)の圧着端子を基に選定しています。
The crimp terminals are selected based on the crimp terminals from Nichifu Co., Ltd.

・注文方法: 型番 (下表の型番を御参照下さい。)

■仕様 Specifications. ・Ordering Form: Type No. (See the type number in the following table)

番号 Part No.	名称 Part Name	材質 Material	寸法 Size	規格 Standard	処理 Treatment
1	基板端子 Printed board Terminal	黄銅 Brass	板厚 t=0.8	C2680R	スズメッキ Tin-Plated
2	結線ビス Screw	鉄 Steel	M3	C2700W	ニッケルメッキ Nickel-Plated

型番 Type No.	納入される物 Product Delivered
FP439A	基板端子(M3用)のみ(ビスなし) Printed board terminal (for M3) only (w/o screws)
FP439AS	基板端子+M3×6Lフリータンシビス組付 Printed board terminal+M3×6L screw attached

対応可能ビス Compatible screw	材質 Material	処理 Treatment	形状 Shape
PW, SWセムスバインド M3×6L Type③With Plain(Flat) washer and spring lock washer M3×6L	黄銅 Brass	ニッケルメッキ Nickel-Plated	Type③
	鉄 steel		
SWセムスバインド M3×6L Type④With spring lock washer M3×6L	黄銅 Brass	ニッケルメッキ Nickel-Plated	Type④
PW, SWセムスナベ M3×7L Type⑤With Plain(Flat) washer and spring lock washer M3×7L	黄銅 Brass	ニッケルメッキ Nickel-Plated	Type⑤
	鉄 steel		
SWセムスナベ M3×7L Type⑦With spring lock washer M3×7L	黄銅 Brass	ニッケルメッキ Nickel-Plated	Type⑦